

# RP12000 E Portable Generator

EPA (502-3699), CARB (502-3700), CSA (502-3701)



12000/ 11000\* W Running | 15000 W Starting

## Features

- Low Harmonic Distortion all copper generator (THD < 5%)
- Built tough with a heavy-duty frame, never-flat wheels and a padded, double-hinged, locking handle
- Easy to set up and operate
- Pressurized oil system
- Enhanced safety features like a USDA Forest Service compliant spark arrestor, automatic low-oil shutdown and added GFCI protection
- Electric start and automatic battery charging when running
- Battery charger included
- Idle Control



Because of continuing improvements, actual product may differ slightly from this photo.

## Control Panel



\*EPA and CARB Models are both rated as 12000 AC Output Running Watts. CSA Model is rated as 11000 AC Output Running Watts.

# RP12000 E Portable Generator

EPA (502-3699), CARB (502-3700), CSA (502-3701)



## Specifications

ENGINE	
Starting Method	Electric
Run Time @ 50% Load	11.7 hours
Idle Control	Automatic
Fuel Tank Nominal Capacity	13.2 gal / 50 L
Fuel Tank Material	Metal
Fuel Type	Unleaded Gasoline $\geq$ 87 octane*
Fuel Gauge	Dial Gauge
Engine Displacement	670 cc
Engine Type	OHV v-twin
Engine Speed	3600 RPM
Lubrication Method	Pressurized
Recommended Oil	SAE 30 or 10W-30
Oil Capacity	1.5 qt / 1.6 L
Region Certifications	EPA, CARB, CSA
Shutdown Method	Automatic Low Oil Level

ELECTRICAL	
Running Power	12000/ 11000** Watts
Starting Power	15000 Watts
AC Output	120V / 240V @ 60 Hz
DC Output	12V (8.3A)
Total Harmonic Distortion (THD)	< 5%
Receptacles	2x 5-20R GFCI Duplex, 1x L5-30R (Twist Lock), 1x L14-30R (Twist Lock), 1x 14-50R, 1x DC 12V 8.3A
Voltage Regulation	Automatic Voltage Regulation (AVR)
Battery Type	Self-Charging Lead Acid

EXTRA FEATURES	
Illuminated Control Panel	Yes
Handle Style	Padded, Double Hinged
Wheel Type	Never-Flat
Indicator Lights	-
USB	-

**WARRANTY** Standard 2-year limited, extended to 3-year limited when registered within 30 days


\*No more than 10% ethanol; fuel stabilizer should also be used for storage

\*\*EPA and CARB Models are both rated as 12000 AC Output Running Watts. CSA Model is rated as 11000 AC Output Running Watts.

## Dimensions and Weights

ASSEMBLED	
Height	35.8 in / 910 mm
Width	32.7 in / 830 mm
Length	35.7 in / 908 mm
Extended Length	48.6 in / 1235 mm
Unit Weight (Dry)	350 lbs / 159 kg

CARTON	
Height	34.4 in / 875 mm
Width	26.0 in / 660 mm
Length	34.1 in / 865 mm
Shipping Weight	397 lbs / 180 kg



© 2018 Caterpillar. All Rights Reserved.  
CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

## Accessories

RP12000 E Cover (501-5294)



RP12000 E Service Kit (501-5293)



Multi Connector Power Cord (25FT) (502-3692)



LEHQ0059-03