## SUNFIRE

HEATS UP TO 2,800 SQ. FT.







**LOW NOISE** 

**ODORLESS** 





ZERO CO EMISSIONS\*

DUST FREE EXPERIENCE







\* Requires 120V of electricity.



THERMOSTAT CONTROL OPTION CONNECT TO STANDARD WALL THERMOSTAT (THERMOSTAT NOT INCLUDED)



## THE ULTIMATE HEATING



Advanced technology extends nozzle life, improve<sub>S</sub> burn efficiency to achieve zero\* carbon monoxide emissions, and includes *RAPID ACCESS™* Easy Maintenance Hatch.

\*Zero CO with properly tuned burner and at steady state temperature.



Allows quick access to the nozzle assembly making tune-ups and maintenance ultra-fast and easy.

Requires proper ventilation indoors. Not for household residential use.

**Multi-Lift Bracket** 

(Hook/Strap/Forklift)

Safety Tip Switch

Thermostat Regulation Option

> Collapsible Handle

Heavy-Duty
Construction

\* Actual product may vary from images due to product enhancement.



Easy-Fill Fuel Neck

Flat-Free

Wheels

**Upward Tilt** 

Capability

**Comfort Grip** 

**Quick Change** 

**Steel Tube Frame** 

Spin-on fuel filter

**Available Accessory:** Fuel-Filter Heating Band. Improves startup in extreme cold conditions.

-	$\Gamma$	<b>`</b>	ΛТ	NI C
-5 P		. I F	$\Delta$	N S

31 LOTITOR TIONS								
BTU/Hr:	120,000	Weight:	120 lbs. Fully Fueled: 218 lbs.	Thermostat Options:				
Fuel:	Diesel, #2 Fuel Oil, Kerosene	Product Dimensions:	32"L x 28.5"W x 33.75"H	Use any mechanical or battery of wall thermostat. Do not use a the that requires 120V of power.				
Flow Rate GPH:	.87 Diesel and .78 Kerosene	Run Time:	16 Hrs. Diesel / 18 Hrs. Kerosene					
Tank Capacity: 14 Gallons		Minimum Clearances:		triat requires 120 v or power.				
Electrical Requirements:	120V 1.2A 60HZ (800W+ Pure Sine INV)	Keep away from combustible items.	Back: N/A	Thermostat not included.				

## **SUNFIRE**







perated ermostat