

# SHUTTLE Z+2

### VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI gas engine or with an ELITE lithium powertrain activated by Samsung SDI lithium technology.



ALL-NEW IMPROVED STYLING

NOW AVAILABLE WITH ELITE LITHIUM POWERTRAIN

**18" OR 20"** TIRE OPTIONS

2 OR 4-WHEEL MECHANICAL BRAKE OPTIONS

CUSHMAN.COM

CUSHMAN<sup>®</sup>



#### STANDARD FEATURES

- RFS Pro Rear-Facing Seat
- Halogen Headlights
- 18" or 20" Tires
- 2-Wheel Mechanical Brakes
- E-Shield™ Frame
- Modular Canopy
- Premium Steering Wheel
- Side Body Color
- Multifunction Gauge (ELiTE only)
- Fuel and Oil Gauge (Gas only)

#### **OPTIONS & ACCESSORIES**

- 4-Wheel Mechanical Brakes
- Contoured Seats
- Limited Slip Differential
- LED Headlights, Taillights and Brake Lights
- Brush Guard
- Lockable Glove Box with Shelf and Molded Rubber Mats
- Fold-Down Windshield
- Flat Windshield
- Weather Enclosure
- USB Outlet
- Rearview Mirror
- ELiTE Lithium 2.2, 4.2, or 6.2 Pack (ELiTE only)
- Rapid On-Board Charger (ELiTE only)

#### CUSHMAN.COM

## SHUTTLE<sup>™</sup> 2+2

	SHUTTLE 2+2 ELITE		SHUTTLE 2+2 GAS		
	18" TIRES	20" TIRES	18" TIRES	20" TIRES	
<b>BODY &amp; CHASSIS</b>		1	1	1	
FRAME	Welder	d Steel with E-Coat &	& DuraShield™ Powc	ler Coat	
BODY & FINISH	Injection Molded TPO				
STANDARD COLOR	Patriot Blue				
DIMENSIONS					
OVERALL LENGTH	113 in (287 cm)				
OVERALL WIDTH	47 in (		119 cm)		
OVERALL HEIGHT (W/ CANOPY)	76 in (193 cm)	80 in (203 cm)	76 in (193 cm)	80 in (203 cm)	
OVERALL HEIGHT (W/O CANOPY)	48 in (122 cm)	52 in (132 cm)	48 in (122 cm)	52 in (132 cm)	
WHEEL BASE	65.5 in (166 cm)				
WHEEL TRACK	37 in (94 cm) Front / 38 in (97 cm) Rear				
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)	4.3 in (11 cm)	5.5 in (14 cm)	
POWER					
POWER SOURCE	56.7V Li-Ion Battery		4-Cycle, 24.5 cu in (401cc)		
VALVE TRAIN	N/A		Single Cylinder OHV		
HORSEPOWER (KW)	11.7 hp (8.7 kW)		13.5 hp (10.1 kW)		
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary		Starter/Generator, Solid State Regulator		
BATTERY (QTY/TYPE)	2.2 Single, 56.7V Li-Ion Composite Module		One, 12V Maintenance Free		
BATTERY CHARGER	56.7V, 350W Domestic Charger, 3M Charging Cord		N/A		
KEY OR PEDAL START		Pe	dal		
AIR CLEANER	N/A		Industrial Rated Dry Filter		
LUBRICATION	N/A		Pressurized Oil System		
OIL FILTER	N/A		Spin-On		
COOLING SYSTEM	N/A		Air Cooled		
FUEL CAPACITY	N/A		5.96 Gallon (22.6 L) tank		
DRIVE TRAIN	Motor Shaft Direct Drive		Continuously Variable Transmission (CVT)		
TRANSAXLE		Differential w,	/ Helical Gears		
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse / Key Switch		Forward - Reverse		
REAR AXLE RATIO	16.99:1		11.47: 1 (Forward) / 14.35:1 (Reverse)		
PERFORMANCE					
SEATING CAPACITY		4-Pe	erson		
WEIGHT W/O BATTERIES	743 lb (342 kg)	782 lb (351 kg)	872 lb (396 kg)	913 lb (414 kg)	
CURB WEIGHT	790 lb (363 kg)	829 lb (372 kg)	902 (409 kg)	963 lb (437 kg	
VEHICLE LOAD CAPACITY	800 lb (363 kg)				
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.76 m)				
SPEED		16.5 mph ± 0.5 mph	(26.5 kph ± 0.8 kph	)	
STEERING & SUSPE	ENSION				
STEERING	Self-Compensating Rack and Pinion				
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers				
	L	Dual Rear Wheel Mechanical Self-adjusting Drum			
SERVICE BRAKE		l Rear Wheel Mecha	nical Self-adjusting I	Drum	
	Dual	l Rear Wheel Mecha If-Compensating, Si		•••••••••••••••••••••••••••••••••••••••	

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2024 and later gas-powered carts. ©2023 Textron Specialized Vehicles Inc. 60009-G8 (Rev. 05/2023)

