



SCISSOR LIFT

MICRO SLIM ELECTRIC



Micro 26™ Electric Scissor Lift

- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 26 ft. (7.6m) Lifts
- 36 in. (90 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Extended Duty Cycle, Smoother Control and Fewer Leak Points
- Spacious 2-Person Platform with 500 lb. (226 kg) Capacity
- Driveable at Full Height
- Fully Proportional Lift and Drive Controls

Reach 32 ft. Height in Tight Work Areas
with Micro Footprint



Standard Features

Work Area

Roll Out Deck Extension with Incremental Locking Positions
 Standard Full Height Swing Gate
 Lanyard Attachments (2)

Performance

Direct Electric Drive
 Fully Proportional Drive and Lift Controls
 Up To 25% Gradeability

Power

24v DC, 240 Ah Battery Pack
 Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components in
 Swing Out Trays
 Parking Brake Release Switch for Towing

Safety

Lift Control Orientation Designed to Avoid Entrapment
 Dedicated Compartments Protect Electrical and Hydraulic Components
 Emergency Shut-Off at Platform and Lower Controls
 Non-Skid Metal Deck Construction
 Descent Alarm
 Drive Speed Interlock
 Multi-Axis Tilt Sensor
 Multiple Disk Brakes
 Scissor Maintenance Lock
 Automatic Parking Brakes
 Automatic Pothole Protection

Other Features

Removable Upper Controls
 Voltage-Compensating Fully Automatic Battery Charger
 Hour Meter
 Machine Tie Downs
 Non-Marking Tires
 All-Motion Alarm
 Fork Lift Pockets
 Flashing Beacon

Optional Features

900W Inverter
 Tool Tray
 Cold Weather Package
 Proactive Platform Safety System (PPSS)
 Leak Containment System™ (LCS)
Patent Pending
 2nd Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark and Micro 26™ and Leak Containment System™ are trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System™ is Patent Pending. 97024 DTD 0419

Micro 26™	U.S.	Metric
Heights		
Working Height*	32 ft.	9.45 m
Platform Height	26 ft.	7.62 m
Stowed Height (Top Guardrail)	90.3 in.	2.3 m
Stowed Height (Rails Folded)	78.75 in.	2 m
Stowed Height (Platform Floor)	47 in.	1.2 m
Guardrail Height	43.5 in	1.1 m
Toeboard Height	6 in.	0.15 m
Ground Clearance (Stowed)	3 in.	7.62 cm
Dimensions		
Length-Stowed (Overall)	74 in.	1.88 m
Length-Stowed (Ladder Removed)	68 in	1.73 m
Chassis Width	31.9 in	.81 m
Platform Length (Extended)	103.5 in.	2.63 m
Platform Length (Retracted)	68 in.	1.73 m
Roll-Out Deck Length	35.5 in.	.9 m
Platform Width (Outside)	29.1 in.	.74 m
Wheelbase	55 in.	1.4 m
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs.	113 kg
Speed		
Raise/Lower Speed	30/25 sec	
Drive Speed (Stowed)	2.5 mph	4 km/h
Drive Speed (Elevated)	.5 mph	.8 km/h
Performance		
Gradeability	25% 14 degrees	
Wind Rating	Indoor Only	
Turning Radius (Inside)	6 in.	15 cm
Weight**	4190 lbs.	1900 kg
Power Source	24 v DC, 240 Ah Battery Pack	
Controls	Proportional	
Tires	12 in. x 5 in	30 cm x 12.5 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated. This machine is indoor rated only.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20-2018 and CSA B354.6.17.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

