


TMC-7	MODEL #	TMC-7-5.5H	TMC-7-2
	PART #	57100	57200
	POWER	Gasoline	Electric
	HORSE POWER	*5.5 HP	2 HP, 115
	PHASE	N/A	Single
	AMPS	N/A	18.4/9.2
	*RPMS	3150	1740
	BELTS	Std "V" Belt	Std "V" Belt
	LENGTH	40"	40"
	WIDTH	24"	24"
TURBO EDGE GRINDER	HEIGHT	38.5"	38.5"
	WEIGHT	120 lbs	130 lbs
STRIP GRIND REMOVE			
			

PRODUCTION RATE: 7" Working Width will grind approximately 400-500 lineal ft. per hour at 1/16" depth with Dyma-Dots. Polishes approximately 500-700 lineal ft. per hour per tooling pass.

INCLUDES: 1 - 7" Multi-Tooling Disc & Standard 2" Vacuum Port. Ridge Head Assembly is Standard on Gas models.

REQUIRES: 3 - Magna-Trap tools, or 1 - 7" Diamond Cup Wheel

RIGID AND FLEX HEAD ASSEMBLIES ARE IDEAL FOR:

- Grinding uneven expansion joints, high spots
- Grinding curbs and gutters for proper flow trenching
- Remove coatings, build-ups, resins and more
- Grind/Polish against any vertical surface walls, corners, columns and tight areas
- Pair with any larger Polishing machine
- 4 position handle and shroud allows maximum control and coverage



TMC-7



DOUBLE DYMA-DOT
Medium Part# QC2B-MC-0030
Soft Part# QC2B-SC-0030



DYMA-SEG
Medium Part# QC2S-MC-0018
Soft Part# QC2S-SC-0018



PCD w/BACKING SEGMENT
LEFT-HAND (Blue) Part# QC-PCD1-LB
(Left-Hand-For use on Single & Dual Disc Grinders)



7" DIAMOND CUP WHEEL
17 Segmented dry cut grinding wheel
40-50 Grit - Part# 72030
150 Grit - Part# 72031

SINGLE DISC TOOLING PACKAGES

PART #	ITEM	DESCRIPTION
M105	Medium Concrete Tooling Rental Package	3 Double Dyma-Dots 3 Dyma-Segs, 3 PCD w/Backing Segment (Left Hand)
M106	Soft Concrete Tooling Rental Package	3 Double Dyma-Dots 3 Dyma-Segs, 3 PCD w/Backing Segment (Left Hand)

STRIP

Flaking Paint, Glue & Adhesive, Soft Thinset, Industrial Buildups, Foam Rubber Carpet Backing

GRIND

Thin Mill Coatings, Concrete Sealers, Hard Thinset, Concrete Imperfections, Light Concrete Leveling

REMOVE

Industrial Strength Coatings, Waterproof Membrane, Hard Coatings, Pool/Cool Deck, Epoxy, Polyurea



THE TMC-7 **GAS** COMES STANDARD WITH A **RIDGID HEAD ASSEMBLY**

THE TMC-7 **ELECTRIC** COMES STANDARD WITH A **FLEX HEAD ASSEMBLY**



* RPM's are based on the machine's accessory speed. * NET HORSEPOWER STATEMENT - *As rated by the engine manufacturer. The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE J1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the opening speed of the engine in application, environmental conditions, maintenance, and other variables. ** Call for availability. **WARNING: CALIFORNIA PROPOSITION 65: Please read page 60 for warnings.**