

980M/982M

Wheel Loaders



*写真は海外仕様機でオプション品を含みます。

| | 980M | 982M |
|-------------------------------------|-------------------------|-------------------------|
| Engine Model | Cat® C13 ACERT™ | Cat C13 ACERT |
| Maximum Power – ISO 14396 | 313 kW | 321 kW |
| Maximum Net Power – ISO 9249 | 288 kW | 297 kW |
| Bucket Capacities | 4.2-12.2 m ³ | 4.6-12.0 m ³ |
| Operating Weight | 30 173 kg | 35 695 kg |



オフロード法2014年
基準適合

RELIABLE, PRODUCTIVE AND FUEL EFFICIENT

- Up to 10% more fuel efficient than the industry leading K Series*
- Up to 25% more fuel efficient than H Series*
- **Performance Series buckets** are easy to load and improve material retention
- **Work tools and coupler ready** provide a wide range of work tools and allow the same work tool on different sizes of wheel loaders
- **Cat engine with ACERT Technology** which meets Japan 2014 (Tier 4 Final) emission standards and includes Cat Clean Emissions Module for continuous and efficient operation
- **Advanced powershift transmission** with a standard lock up clutch torque converter and lock-to-lock shifting delivers smooth shifts, fast acceleration and speed on grade
- **Next generation axles** with optional limited slip differentials to provide optimal traction in varying underfoot conditions for improved productivity
- **Next generation load-sensing hydraulic system** to provide optimal control of machine functions

EASE OF OPERATION

- **Best-in-class operator environment** for unmatched operator comfort and efficiency
- **Advanced technology with Cat Connect** to monitor, manage and enhance job site operations

SERVICE ACCESS

- **Legacy one-piece hood, centralized service centers, windshield cleaning platform and harness tie-off** to provide the best in class service access

Contents

| | |
|-------------------------------|----|
| Reliable | 4 |
| Durable | 5 |
| Productive | 6 |
| Fuel Efficient | 7 |
| Easy to Operate | 8 |
| Versatile | 10 |
| Integrated Technologies | 12 |
| Owning Costs | 14 |
| Operating Costs | 15 |
| Serviceable | 16 |
| Sustainable | 17 |
| Customer Support | 17 |
| Specifications | 18 |
| Standard Equipment | 32 |
| Optional Equipment | 33 |
| Notes | 34 |



**Fuel efficiency is measured in mass of material moved per volume of fuel burned. Average efficiency improvement as tested and analyzed for an average composite cycle and standard configuration with variations per comparable model with and without Economy Mode active. Factors influence result variation such as, but not limited to, machine configuration, operator technique, machine application, climate, etc.*



The new 980M and 982M Wheel Loaders have a Japan 2014 (Tier 4 Final) ACERT engine equipped with a combination of proven electronic, fuel, air and aftertreatment components. Applying proven technologies systematically and strategically lets us meet our customer's high expectations for productivity and fuel efficiency. Deep system integration results in reduced emissions, improved performance and improved fuel economy without interrupting machine performance making it seamless to operators. M Series Loaders are up to 10% more fuel efficient than the K Series Loaders and up to 25% more efficient than the H Series Loaders they replace.* The reliability, durability, and versatility of both the 980M and 982M result in machines that are better built to meet your needs.

Thanks to its longer lift arm and higher hinge pin height compared to 980M, the new 982M excels in loading trailer dump trucks (which have a large capacity body) in quarry yards, small 36 tons rigid trucks or mobile breakers in quarry pits and large articulated trucks on construction sites. With larger buckets and other available work tools, the 982M will also boost production and fuel efficiency in coal handling and industrial applications, providing you with an exciting new option in this size class.

Reliable

Proven Components and Technology You Can Count On.



Japan 2014 (Tier 4 Final) engine is equipped with a combination of proven electronic, fuel, air and aftertreatment components.

More Powerful, Reliable Engine Electronics

The electronics used in Cat Japan 2014 (Tier 4 Final) engines are more powerful and robust than ever. Increased features and connection commonality improve the customer experience and increase quality and reliability. Over-foam wiring harness adds to reliability even in the most demanding applications.

Hydraulics

The 980M and 982M hydraulic systems have significant design changes and customer value improvements. The main hydraulic valve is now a mono-block with an integrated ride control section. The mono-block design reduces weight, has forty percent fewer leak points and is common across all M Series models. The auxiliary third function can be easily added at the factory or in the field with the addition of a second remote valve.

Equipment Monitoring

Cat Connect technologies and Cat dealer services take the guesswork out of equipment management. Product Link™ and the online VisionLink® application enable you to monitor real-time machine data and manage machines health. Your Cat dealer offers expert advice and S-O-SSM Services to maintain equipment reliability and efficiency.

Cold Start Package

The new optional cold start package provides dependable starts in extreme cold weather and high altitudes.

Durable

Better Designed to Meet Your Needs.



Frames

The robotically welded two-piece structural frame design provides strong and rigid structures that absorb all the forces associated to penetration, loading and twisting.

The M Series articulating hitch system, joining the front and rear frames, provides increased bearing force capacity.

Axles

The M Series axles are designed to handle extreme applications resulting in reliable performance and durable life. The rear axle can oscillate to ± 13 degrees helping to ensure all four wheels stay on the ground providing stability even in the roughest terrain, for excellent stability and traction.

Productive

Work Smart and Move More.



The right technologies fine-tuned for the right applications result in:

- **Improved Fluid Efficiency** – Up to 5% improvement over Japan 2011 (Tier 4 interim) products (including Diesel Exhaust Fluid consumption).
- **High Performance** across a variety of applications.
- **Enhanced Reliability** through commonality and simplicity of design.
- **Maximized Uptime and Reduced Cost** with world-class support from the Cat dealer network.
- **Minimized Impact of Emission Systems** – Designed to be transparent to the operator without requiring interaction.
- **Durable Designs** with long life to overhaul.
- **Delivering Better Fuel Economy** with minimized maintenance costs while providing the same great power and response.

Hydraulics

The new ride control system now has two accumulators enabling it to be more effective over a greater payload range, increasing productivity and operator efficiency due to a better ride.

The next generation implement pump continuously and automatically balance hydraulic loads with the machine performance desired by the operator.

Transmission

The 980M and 982M power trains have been improved with the addition of a lock-up clutch torque converter standard. These new torque converters have been matched with the engine power and hydraulics to improve performance and fuel efficiency. These rugged planetary transmissions also have a new split-flow oil system which use new multi-viscosity oil to improve fuel economy.

Axles

In addition to aggregates, sand and gravel and asphalt or concrete plants, these models are commonly used in heavy construction applications where poor underfoot conditions make traction difficult slowing production and challenging job deadlines. The optional limited slip differentials will improve tractive ability in these applications thereby increasing productivity.

The axles have new external caliper disc parking brakes mounted to the input shaft of the front axles. Since they are external, they do not have the inefficiencies of enclosed wet parking brakes due to brake discs running in oil nor is there any oil to change reducing fuel and maintenance costs. External caliper parking brakes are easily accessible for inspection and service.

Fuel Efficient Engineered to Lower Your Operating Costs.

Engine and Emissions

The Cat C13 ACERT engine is designed for maximum fuel efficiency and increased power density, while meeting Japan 2014 (Tier 4 Final) emission standards. This engine features innovative Cat electronics, fuel injection process, air-management systems, aftertreatment solution with Cat Selective Catalytic Reduction, and a fuel efficient regeneration system. For Japan 2014 (Tier 4 Final) equivalent emissions solutions, the Cat Regeneration System automatically removes soot from the Diesel Particulate Filter without interrupting your machine's work cycle.

Efficient Systems and Components

Innovative systems intelligently lower the average working engine speeds and reduce the overall system heat loads which result in significantly improved performance and fuel efficiency.

Advanced Systems with Innovative Integration

The deep system integration of the new engine and emissions system, power train, hydraulic system and cooling system result in 10% lower fuel consumption on average compared to the 980K.

Economy Mode

The productive economy mode automatically controls the engine torque and speed based on the machine's power train load and places engine speed and torque in the most efficient operating range. The result is improved fuel efficiency while delivering optimal performance.



Next Generation Fuel Systems

Cat injection timing precisely controls the fuel injection process through a series of carefully timed microbursts, providing more control of combustion for the cleanest, most efficient fuel burn. On 980M and 982M the MEUI™ fuel systems boost performance and reduce soot for the C13 ACERT engine.

Cat NO_x Reduction System

The Cat NO_x Reduction System (NRS) captures and cools a small quantity of exhaust gas, then routes it back into the combustion chamber where it drives down combustion temperatures and reduces NO_x emissions.

Aftertreatment Technologies

To meet the additional 80% reduction in NO_x emissions required by Japan 2014 (Tier 4 Final) emission standards, one new system, the Selective Catalytic Reduction (SCR), has been added to the already proven Cat Japan 2011 (Tier 4 interim) aftertreatment solution.

Easy to Operate

Safe. Comfortable. Efficient.



Ensuring operators are safe, confident in the control of their machines, have a clean, comfortable and quiet operating environment with controls that are intuitive and low effort all contribute to lower operator fatigue and better performance.

Cab Access

A switch has been added to the electronic service center which unlatches the door remotely (optional). The gas strut then swings the door open. The angle of the steps up to the cab has been increased to an optimal fifteen degrees enabling operators to walk up like stairs versus climbing more vertically like a ladder. Grab handles have been repositioned so a secure three points of contact can be maintained at all times.

Visibility

Once in the cab, the new door securely seals against the new roll formed ROPS posts and the lower glass panel has been extended several inches to improve visibility to the left side of the machine. New larger convex mirrors improve visibility to the rear and integrated spot mirrors provide visibility close to both sides of the machine.

Sound and Vibration

The Cat air suspended seat, the viscous cab mount combined with lower engine speeds and an improved ride control system decrease noise and vibration the operator is subjected to, allowing him to remain efficient and productive the whole day long.



Central Display

The central display panel has a large text box, five analog gauges, and LED warning indicators. The large text box provides in-language information about machine operation, feature activation and system troubleshooting and calibration. With the five large analog gauges the operator can easily identify if key systems are within normal operating range.



Touch Screen Display

A new multipurpose color touch screen display dramatically simplifies the operator interface; with machine controls, rear vision camera and new fully integrated Cat Production Measurement system. Intuitive navigation with in-language text enables operators to modify certain machine operating parameters and monitor machine conditions literally at the touch of their fingers.

Control Panel

Sealed against moisture and dirt, the centralized switch panel with LEDs provides reliability and ready access to frequently required functions, even while wearing gloves. The ISO symbols located on each membrane switch are molded all the way through to ensure the image will not wear off over time.

The M Series maintains the “help” feature which explains the function of each membrane switch.

Focusing on operator efficiency, the control panel has been streamlined to include easy to reach highly utilized machine controls. The touch screen display enables the relocation of some expanded functions while eliminating the need for a second switch panel for further simplicity and easy machine operation.



Electro-Hydraulic (EH) Joystick Steering with Force Feedback (Speed Sensitive)

Your operators will enjoy and quickly adapt to the industry leading seat mounted EH joystick steering system, which provides precision control and dramatically decreases operator arm fatigue. For operators who prefer a steering wheel, an electro-hydraulic steering wheel is available as an option.

Implement Controls (EH)

Seat mounted single axis implement control levers provide your operator with precise control of the work tool, all while moving with the seat for maximum comfort. In-cab programmable kick-outs and automatic cylinder snubbing are easy to set on-the-go for tilt, lower and lift, ideal for repeatable cycles.



Ride Control

The next generation ride control works as a shock absorber, improving ride quality and smoothness over rough terrain, increasing your operator confidence, comfort and efficiency, ensuring excellent material retention.

Versatile

Linkage and Guard Options to Meet Your Various Applications Needs.



Z-bar Linkage

The proven Z-bar linkage combines digging efficiency with excellent visibility to the tool resulting in excellent penetration into the pile, high breakout forces and superior production capabilities.

High Lift Linkage

The optional high lift linkage on 980M offers increased hinge pin height to load more easily in a variety of applications with any type of bucket or fork.

Aggregate Handler

Aggregate packages are specialized offerings for specific loose aggregate rehandling applications, such as truck loading, hopper charging, stockpiling, and load and carry. Rehandling loose aggregate is less stressful to the machine, therefore payloads can be increased above other applications by installing larger buckets, counterweights and a scale system such as the Cat Production Measurement system.

To do so, the Cat aggregate packages require some prerequisites in terms of correct application, machine configuration and conformance to Caterpillar payload policy. Misapplication of Aggregate Handlers may result in significant reliability and durability risk.*

**Please consult your Cat dealer to ensure proper machine configuration selection in conformance to Caterpillar payload policy.*

Versatile

Do More Jobs with One Machine. Work Tool Options to Meet Your Needs.



An extensive range of work tools and bucket styles are available to customize these machines for your operation. Work tools are available either with pin on or quick coupler interface.

Performance Series Buckets

- **Load Easy, Fuel Efficient, Carry More** – Performance Series Buckets utilize a system-based approach to balance bucket shape with the machine's linkage, weight, lift and tilt capacities. Operators benefit from reduced dig times and better material retention; ultimately translating into significant productivity and fuel efficiency improvements.
- **Lower Operating Costs** – Performance Series Buckets feature a longer floor that easily digs through the pile and provides excellent visibility for the operators to see when the bucket is full. Less time digging in the pile results in lower fuel consumption and improved tire life. A unique spill guard protects the cab and linkage components from material overflow.
- **Higher Productivity** – Performance Series Buckets achieve higher fill factors – ranging from 100% to 115% depending on the machine application and material type. The buckets feature a curved side profile to maximize material retention. The optimized design results in unsurpassed production capabilities.
- **Styles and Applications** – Performance Series Buckets are available for General Purpose, Material Handling, Rock, Heavy Duty Rock and Coal style buckets.

Specialty Buckets

- **Heavy Duty Quarry Rock Buckets** are designed for bank or face loading material where high impact/high abrasion is encountered. Buckets include thicker base edge, liner package and addition wear plates.
- **Slag Buckets** are designed for use in steel mills and slag processing centers. They feature increased material thickness in critical structural components to provide maximum durability for hot or cold slag handling.
- **Waste Handling Buckets** are designed to move large volumes of low-density waste in transfer stations, landfills and recycling yards. Large capacities give maximum production when loading conveyors, trucks or hoppers.
- **Woodchip Buckets** are optimized for moving large volumes of wood chips in forestry and millyard settings. They feature a flat floor and straight edge designed to scoop the bucket full and help heap the load high.

Quick Couplers and Work Tool Attachments

A Wheel Loader equipped with a quick coupler is a much more versatile machine. Buckets and work tools can be changed without leaving the cab – allowing the machine to quickly move from task to task.

- **Pallet Forks** are available for material handling.
- **Millyard and Logging Forks** are available for forestry applications.
- **Specialty Work Tool Attachments** such as plows for snow removal are available. Contact your local Cat dealer for more details on tools available for your application.



Integrated Technologies

Monitor, Manage, and Enhance Job Site Operations.

Cat Connect makes smart use of technology and services to improve your job site efficiency. Using the data from technology-equipped machines, you'll get more information and insight into your equipment and operations than ever before.

Cat Connect technologies offer improvements in these key areas:



EQUIPMENT
MANAGEMENT

Equipment Management – increase uptime and reduce operating costs.



PRODUCTIVITY

Productivity – monitor production and manage job site efficiency.



SAFETY

Safety – enhance job site awareness to keep your people and equipment safe.


Featured Cat Connect technologies include:

Cat Connect LINK Technologies

LINK technologies wirelessly connect you to your equipment giving you access to essential information you need to know to run your business. Link data can give you valuable insight into how your machine or fleet is performing so you can make timely, fact-based decisions that can boost job site efficiency and productivity.

Product Link/VisionLink

Product Link is deeply integrated into your machine to take the guesswork out of equipment management. Easy access to timely information like machine location, hours, fuel usage, idle time and event codes via the online VisionLink user interface can help you effectively manage your fleet and lower operating cost.



PAYLOAD Technologies

PAYLOAD technologies provide accurate weighing of materials being loaded and hauled. Payload data is displayed for loader operators in real-time to improve productivity, reduce overloading, and recorded to track material movement by shift.

Cat Production Measurement 2.0 (Optional)

- Brings payload weighing to the cab, enabling operators to weigh loads “on-the-go” during loading operations.
- Integrated Cat multi-function touchscreen display with graphical user interface is easy to understand and adds no clutter to the cab.
- Easy calibration procedure requires no special tools and reduces operational complexity.
- Low Lift Weigh and Tip-off features enable faster loading of trucks to their maximum capacity.
- VisionLink common back-office interface provides you a quick summary of loader operations, including payload productivity and efficiency.
- Optional Advanced Productivity subscription provides comprehensive actionable information to help you manage and improve the productivity and profitability of your operations.



DETECT Technologies

DETECT technologies enhance operator awareness of the environment around working equipment and provide alerts to help keep people and assets safe.

Rear Vision Camera

- Integrated into standard display, enhances visibility behind the machine helping you work confidently.
- Optional second display can be added to provide a dedicated rear view of the job site.

Rear Object Detection (Optional)

- Integrated into touchscreen display, the radar system warns an operator of an object in critical zone while going in reverse.
- Increased awareness of the working environment enhances site safety.

Owning Costs

Proven Best Investment.

Customer Support Agreements

A Customer Support Agreement (CSA) is an arrangement between you and your Cat dealer that helps you lower your total cost per ton. CSAs are flexible, allowing them to be tailored to your business needs. They can range from simple Preventive Maintenance Kits to elaborate Total Cost Performance Guarantees. Having a CSA with your Cat dealer enables more time for you to do what you do best – run your business.

Monitoring Systems

Monitoring product health is key to optimizing the life of an investment into a Cat Wheel Loader.

- **Cat Product Link** – Cat Product Link allows remote monitoring of equipment to improve overall fleet management effectiveness. Product Link is deeply integrated into machine systems. Events and diagnostic codes, as well as hours, fuel, idle time and other detailed information are transmitted to a secure web based application, VisionLink. VisionLink includes powerful tools to convey information to users and dealers, including mapping, working and idle time, fuel level and more.



- **S-O-S Services** – Helps manage component life and decrease machine downtime, increasing productivity and efficiency. Regular fluid sampling can help track what is going on inside your machine. Wear related problems are predictable and easily repairable. Maintenance can be done to accommodate your schedule, resulting in increased uptime and flexibility in maintenance repairs before failure.

Parts Availability

Caterpillar provides an unsurpassed level of personalized service to help you work more cost effectively and efficiently. By utilizing a worldwide parts network Cat dealers help minimize machine downtime and save money by fast delivery of replacement parts.

Resale Value

Owning quality equipment is an important factor in maintaining resale value. Caterpillar is not only known for machines that are better built, but provides product and dealer support to maintain the reliability and durability of your machine.

Operating Costs

Save Time and Money by Working Smart.



Machine configuration, operator technique, and job site layout can impact fuel consumption by as much as 30 percent. Data from customer machines show Cat wheel loaders are the most fuel efficient machines in the industry. Several features contribute to this excellent fuel efficiency:

- **New M Series Japan 2014 (Tier 4 Final) Engine, Hydraulics, Transmission and Ride Control** – Deep system integration results in reduced emissions, more productivity, lower fuel consumption, without interrupting machine performance – making it seamless to you and your operators. Machine requires Ultra Low Sulfur Diesel (ULSD) and DEF.
- **Optional Limited Slip Differentials** – Increase traction, reduce tire scuffing compared to other traction aids, further reducing your operating costs.

- **New External Caliper Disc Parking Brakes** – Easily accessible for maintenance.
- **Lock-up-Clutch Torque Converter and Shift Strategy** – Reduced torque interruption increases driveline efficiency, conserving fuel. Auto 1-4 transmission mode keeps engine rpm low, reducing fuel consumption while delivering optimal machine performance.
- **Machine Configuration** – Select the correct linkage, guarding, work tool and tire type based on machine application. Radial tires are preferred; ensure proper inflation pressures. Heavier tires burn more fuel.
- **Performance Series Buckets** – Deliver faster fill times and better material retention, ultimately reducing cycle times while improving productivity and fuel efficiency.

Enabling Application Efficiency

- **Loading Bucket** – Load in first gear and keep engine rpm low. Raise and tilt bucket smoother, with Caterpillar's multi-function capability, and do not use a "pumping" motion. Avoid lift lever detent and use of transmission neutralizer. Use programmable kick-outs and automatic cylinder snubbing during repeated cycles.
- **Loading Truck or Hopper** – Do not raise the work tool any higher than necessary. Keep engine rpm low and unload in controlled manner.
- **Idle** – Set the parking brake to engage Engine Idle Management System to conserve fuel.
- **Job Site Layout** – Spot loading targets in the right position. Avoid traveling more than twice the machine length during short cycle loading. Reduce transport distance for load and carry cycles by optimizing job site layout.

Serviceable

Easy to Maintain. Easy to Service.

Engine Access

The Cat sloped “one-piece” tilting hood provides industry leading access to the engine. Its design has further been improved on all M Series wheel loaders to provide the best-in-class service access to engine, oil levels and coolant sight gauge.

Cooling System

The cooling system ① is readily accessible for clean out and maintenance. With six cooling fins per 25.4 mm and a perforated grill, most airborne debris entering the system passes through the cooler cores. The hydraulic and A/C cooler cores swing out providing easy access to both sides for cleaning. An access panel on the left side of the cooling package swings down to provide access to the back side of the engine coolant and Air-to-Air After Cooler (ATAAC). An optional variable pitch fan can automatically purge the cooler cores by periodically reversing the airflow when needed.

Service Centers

The electrical and hydraulic service centers provide grouped ground level access to numerous features, enhancing safety and convenience for your operators and service technicians, while reducing service time.

The hydraulic service centers ② are now virtually identical for the M Series product line. This new consistent layout makes it easier for service technicians who work on a variety of M Series models.

The electrical service center ③, located beneath the left platform, contains the maintenance free batteries, a fuse relay panel, main disconnect switch, engine shutdown switch, hood tilt switch, and the jump start receptacle.

Hydraulic system components on the 980M and 982M are protected by full flow and kidney-loop filtration. A filter in the hydraulic tank return line filters all of the oil returning to the tank. There is also a case drain screen for additional protection and finally, a separate kidney-loop filter with a finer micron rating continuously filters smaller particles out of the system. This multilevel design ensures the hydraulic oil is clean and thoroughly protects the rest of the hydraulic system from contamination. A new thermal bypass valve has been added to improve hydraulic system warm-up.



Sustainable Conserving Resources.

The 980M and 982M are designed to compliment your business plan, reduce emissions and minimize the consumption of natural resources.

- Improved fuel efficiency – less fuel consumed results in lower emissions.
- Improved operator efficiency through enhanced visibility and reduced noise levels.
- Link technologies enable you to collect and analyze equipment and job site data so you can maximize productivity and reduce costs.
- Major components are rebuildable, eliminating waste and saving money by giving the machine and/or major components a second life – and even a third life.



Customer Support Unmatched Support Makes the Difference.



Renowned Cat Dealer Support

- Your Cat dealer is ready to help you every step of the way. From new or used machine sales, to rental or rebuild options, your Cat dealer can provide an optimal solution to your business needs.
- Unsurpassed worldwide parts availability, trained technicians and customer support agreements maximize your machine uptime.
- Financing options are offered to meet a variety of customer needs.

980M/982M Wheel Loaders Specifications

Engine – 980M

| | |
|--------------------------------|---------------|
| Engine Model | Cat C13 ACERT |
| Maximum Power (1,700 rpm) | |
| ISO 14396 | 313 kW |
| Maximum Net Power (1,700 rpm) | |
| ISO 9249 | 288 kW |
| Rated Net Power (1,700 rpm) | |
| ISO 9249 | 285 kW |
| Peak Gross Torque (1,200 rpm) | |
| SAE J1995 | 2206 N·m |
| Peak Torque (1,200 rpm) | |
| ISO 14396 | 2182 N·m |
| Maximum Net Torque (1,100 rpm) | |
| ISO 9249 | 2054 N·m |
| Bore | 130 mm |
| Stroke | 157 mm |
| Displacement | 12.5 L |

- Cat engine with ACERT Technology – meets Japan 2014 (Tier 4 Final) emission standards.
- The power ratings apply at the stated speed when tested under the reference conditions for the specified standards.
- The net power advertised is the power available at the flywheel when the engine is equipped with fan, alternator, air cleaner and aftertreatment.
- The gross power advertised is with the fan at maximum speed.

Buckets – 980M

| | |
|-------------------|-------------------------|
| Bucket Capacities | 4.2-12.2 m ³ |
|-------------------|-------------------------|

Weight – 980M

| | |
|------------------|-----------|
| Operating Weight | 30 173 kg |
|------------------|-----------|

• Weight based on a machine configuration with Bridgestone 29.5R25 VSNT L4 radial tires, full fluids, operator, standard counterweight, roading fenders, Product Link, open differential axles (front/rear), secondary steering, sound suppression, and a 5.7 m³ general purpose bucket with BOCE.

Engine – 982M

| | |
|--------------------------------|---------------|
| Engine Model | Cat C13 ACERT |
| Maximum Power (1,700 rpm) | |
| ISO 14396 | 321 kW |
| Maximum Net Power (1,700 rpm) | |
| ISO 9249 | 297 kW |
| Rated Net Power (1,700 rpm) | |
| ISO 9249 | 290 kW |
| Peak Gross Torque (1,200 rpm) | |
| SAE J1995 | 2206 N·m |
| Peak Torque (1,200 rpm) | |
| ISO 14396 | 2182 N·m |
| Maximum Net Torque (1,100 rpm) | |
| ISO 9249 | 2054 N·m |
| Bore | 130 mm |
| Stroke | 157 mm |
| Displacement | 12.5 L |

- Cat engine with ACERT Technology – meets Japan 2014 (Tier 4 Final) emission standards.
- The power ratings apply at the stated speed when tested under the reference conditions for the specified standards.
- The net power advertised is the power available at the flywheel when the engine is equipped with fan, alternator, air cleaner and aftertreatment.
- The gross power advertised is with the fan at maximum speed.

Buckets – 982M

| | |
|-------------------|-------------------------|
| Bucket Capacities | 4.6-12.0 m ³ |
|-------------------|-------------------------|

Weight – 982M

| | |
|------------------|-----------|
| Operating Weight | 35 695 kg |
|------------------|-----------|

• Weight based on a machine configuration with Bridgestone 875/65R29 VLTS L4 radial tires, full fluids, operator, standard counterweight, roading fenders, Product Link, open differential axles (front/rear), secondary steering, sound suppression, and a 6.4 m³ general purpose bucket with BOCE.

980M/982M Wheel Loaders Specifications

Operating Specifications – 980M

Static Tipping Load – Full 40° Turn

| | |
|----------------------|-----------|
| With Tire Deflection | 19 334 kg |
| No Tire Deflection | 20 567 kg |
| Breakout Force | 213 kN |

- For a machine configuration as defined under “Weight.”
- Full compliance to ISO 143971:2007 Sections 1 thru 6, which requires 2% verification between calculations and testing.

Transmission – 980M

| | |
|-----------|-----------|
| Forward 1 | 6.9 km/h |
| Forward 2 | 13.3 km/h |
| Forward 3 | 23.5 km/h |
| Forward 4 | 39.5 km/h |
| Reverse 1 | 7.8 km/h |
| Reverse 2 | 15.2 km/h |
| Reverse 3 | 26.9 km/h |
| Reverse 4 | 39.5 km/h |

- Maximum travel speed in standard vehicle with empty bucket.

Sound – 980M

The sound values indicated below are for specific operating conditions only. Machine and operator sound levels will vary at different engine and/or cooling fan speeds. Hearing protection may be needed when the machine is operated with a cabin that is not properly maintained, or when the doors and/or windows are open for extended periods or in a noisy environment.

| | |
|---|------------|
| Operator Sound Pressure Level (ISO 6396:2008) | 72 dB(A) |
| Exterior Sound Power Level (ISO 6395:2008) | 109 dB(A)* |
| Exterior Sound Pressure Level (SAE J88:2013) | 78 dB(A)** |

*For a standard machine configuration, measured according to the procedures specified with the cooling fan speed set at 70% of maximum value.

**For a standard machine configuration, measured according to the procedures specified. The measurement was conducted under the following conditions: distance of 15 m, moving forward in second gear ratio with the cooling fan speed set at maximum value.

Operating Specifications – 982M

Static Tipping Load – Full 40° Turn

| | |
|----------------------|-----------|
| With Tire Deflection | 20 881 kg |
| No Tire Deflection | 22 201 kg |
| Breakout Force | 253 kN |

- For a machine configuration as defined under “Weight.”
- Full compliance to ISO 143971:2007 Sections 1 thru 6, which requires 2% verification between calculations and testing.

Transmission – 982M

| | |
|-----------|-----------|
| Forward 1 | 6.2 km/h |
| Forward 2 | 11.9 km/h |
| Forward 3 | 21.1 km/h |
| Forward 4 | 37.5 km/h |
| Reverse 1 | 7.0 km/h |
| Reverse 2 | 13.6 km/h |
| Reverse 3 | 24.1 km/h |
| Reverse 4 | 39.5 km/h |

- Maximum travel speed in standard vehicle with empty bucket.

Sound – 982M

The sound values indicated below are for specific operating conditions only. Machine and operator sound levels will vary at different engine and/or cooling fan speeds. Hearing protection may be needed when the machine is operated with a cabin that is not properly maintained, or when the doors and/or windows are open for extended periods or in a noisy environment.

| | |
|---|------------|
| Operator Sound Pressure Level (ISO 6396:2008) | 72 dB(A) |
| Exterior Sound Power Level (ISO 6395:2008) | 109 dB(A)* |
| Exterior Sound Pressure Level (SAE J88:2013) | 78 dB(A)** |

*For a standard machine configuration, measured according to the procedures specified with the cooling fan speed set at 70% of maximum value.

**For a standard machine configuration, measured according to the procedures specified. The measurement was conducted under the following conditions: distance of 15 m, moving forward in second gear ratio with the cooling fan speed set at maximum value.

980M/982M Wheel Loaders Specifications

Hydraulic System

| | |
|--|------------------------------|
| Implement Pump Type | Variable Displacement Piston |
| Implement System | |
| Maximum Pump Output (2,250 rpm) | 449 L/min |
| Maximum Operating Pressure | 34 300 kPa |
| Optional 3 rd Function Maximum Flow | 240 L/min |
| Optional 3 rd Function Maximum Pressure | 21 780 kPa |
| Hydraulic Cycle Time with Rated Payload: | |
| Raise from Carry Position | 5.3 Seconds |
| Dump, at Maximum Raise | 1.7 Seconds |
| Lower, Empty, Float Down | 3.1 Seconds |
| Total | 10.1 Seconds |

Brakes

| | |
|--------|-------------------------------------|
| Brakes | Brakes meet ISO 3450:2011 standards |
|--------|-------------------------------------|

Axles

| | |
|------------------------------------|------------------------------|
| Front | Fixed |
| Rear | Oscillating ± 13 degrees |
| Maximum Single-Wheel Rise and Fall | |
| 980M | 549 mm |
| 982M | 571 mm |

Cab

| | |
|-----------|---|
| ROPS/FOPS | ROPS/FOPS meet ISO 3471:2008 and ISO 3449:2005 Level II standards |
|-----------|---|


Service Refill Capacities

| | |
|--|-------|
| Fuel Tank | |
| 980M | 426 L |
| 982M | 426 L |
| DEF Tank | 21 L |
| Cooling System | 53 L |
| Crankcase | 37 L |
| Transmission | |
| 980M | 77 L |
| 982M | 77 L |
| Differentials and Final Drives – Front | |
| 980M | 84 L |
| 982M | 92 L |
| Differentials and Final Drives – Rear | |
| 980M | 84 L |
| 982M | 92 L |
| Hydraulic Tank | 153 L |

980M/982M Wheel Loaders Specifications

980M Dimensions

All dimensions are approximate.



| | Standard Lift | High Lift |
|---|---------------|------------|
| 1 Height to Axle Centerline | 892 mm | 892 mm |
| 2 Height to Top of Hood | 3110 mm | 3110 mm |
| 3 Height to Top of Exhaust Pipe | 3746 mm | 3746 mm |
| 4 Height to Top of ROPS | 3813 mm | 3813 mm |
| 5 Height to Top of Product Link Antenna | 3891 mm | 3891 mm |
| 6 Height to Top of Warning Beacon | 4112 mm | 4112 mm |
| 7 Ground Clearance | 453 mm | 453 mm |
| 8 Center Line of Rear Axle to Edge of Counterweight | 2469 mm | 2469 mm |
| 9 Center Line of Rear Axle to Hitch | 1900 mm | 1900 mm |
| 10 Wheelbase | 3800 mm | 3800 mm |
| 11 Overall Length (without bucket) | 7964 mm | 8164 mm |
| 12 Shipping Length (with bucket level on ground)*† | 9577 mm | 9778 mm |
| 13 Hinge Pin Height at Carry Height | 621 mm | 678 mm |
| 14 Hinge Pin Height at Maximum Lift | 4539 mm | 4760 mm |
| 15 Lift Arm Clearance at Maximum Lift | 3795 mm | 4010 mm |
| 16 Dump Clearance at Maximum Lift and 45° Discharge*† | 3204 mm | 3425 mm |
| 17 Reach at Maximum Lift and 45° Discharge*† | 1529 mm | 1532 mm |
| 18 Dump Angle at Maximum Lift and Dump (on stops)* | 52 degrees | 55 degrees |
| 19 Rack Back at Maximum Lift* | 61 degrees | 61 degrees |
| 20 Rack Back at Carry Height* | 48 degrees | 48 degrees |
| 21 Rack Back at Ground* | 40 degrees | 39 degrees |
| 22 Clearance Circle (dia) to Counterweight | 13 700 mm | 13 700 mm |
| 23 Clearance Circle (dia) to Outside of Tires | 14 774 mm | 14 774 mm |
| 24 Clearance Circle (dia) to Inside of Tires | 8284 mm | 8284 mm |
| 25 Maximum Width over Tires (unloaded) | 3243 mm | 3243 mm |
| Maximum Width over Tires (loaded) | 3265 mm | 3265 mm |
| 26 Tread Width | 2440 mm | 2440 mm |

*With 5.7 m³ general purpose pin on bucket with BOCE (see Operating Specifications for other buckets)


†Dimensions are listed in Operating Specification charts.

All height and tire related dimensions are with Bridgestone 29.5R25 VSNT L4 radial tires and standard counterweight (see Dimension Changes – Tires chart for other tires). "Width over Tires" dimensions are over the bulge and include growth.

980M/982M Wheel Loaders Specifications

982M Dimensions

All dimensions are approximate.



| | Standard Lift |
|---|----------------------|
| 1 Height to Axle Centerline | 874 mm |
| 2 Height to Top of Hood | 3083 mm |
| 3 Height to Top of Exhaust Pipe | 3719 mm |
| 4 Height to Top of ROPS | 3786 mm |
| 5 Height to Top of Product Link Antenna | 3864 mm |
| 6 Height to Top of Warning Beacon | 4085 mm |
| 7 Ground Clearance | 426 mm |
| 8 Center Line of Rear Axle to Edge of Counterweight | 2716 mm |
| 9 Center Line of Rear Axle to Hitch | 1900 mm |
| 10 Wheelbase | 3800 mm |
| 11 Overall Length (without bucket) | 8584 mm |
| 12 Shipping Length (with bucket level on ground)*† | 10 218 mm |
| 13 Hinge Pin Height at Carry Height | 790 mm |
| 14 Hinge Pin Height at Maximum Lift | 4743 mm |
| 15 Lift Arm Clearance at Maximum Lift | 3884 mm |
| 16 Dump Clearance at Maximum Lift and 45° Discharge*† | 3327 mm |
| 17 Reach at Maximum Lift and 45° Discharge*† | 1602 mm |
| 18 Dump Angle at Maximum Lift and Dump (on stops)* | 50 degrees |
| 19 Rack Back at Maximum Lift* | 57 degrees |
| 20 Rack Back at Carry Height* | 48 degrees |
| 21 Rack Back at Ground* | 42 degrees |
| 22 Clearance Circle (dia) to Counterweight | 13 950 mm |
| 23 Clearance Circle (dia) to Outside of Tires | 15 026 mm |
| 24 Clearance Circle (dia) to Inside of Tires | 8148 mm |
| 25 Maximum Width over Tires (unloaded) | 3452 mm |
| Maximum Width over Tires (loaded) | 3499 mm |
| 26 Tread Width | 2540 mm |

*With 6.4 m³ general purpose pin on bucket with BOCE (see Operating Specifications for other buckets)

†Dimensions are listed in Operating Specification charts.

All height and tire related dimensions are with Bridgestone 875/65R29 VLTS L4 radial tires and standard counterweight (see Dimension Changes – Tires chart for other tires). "Width over Tires" dimensions are over the bulge and include growth.

980M/982M Wheel Loaders Specifications

980M Tire Option Chart

| Tire Brand | Michelin | Michelin | Bridgestone | Bridgestone | Bridgestone | Bridgestone |
|---|----------------|----------------|----------------|----------------|----------------|----------------|
| Tire Size | 29.5R25 | 29.5R25 | 29.5R25 | 29.5R25 | 29.5-25 | 29.5-25 |
| Tread Type | L-5 | L-3 | L-5 | L-3 | L-4 | L-3 |
| Tread Pattern | XLDD2 | XHA2 | VSDL | VJT | RLS | VL2 |
| Width over Tires – Maximum (unloaded)* | 3268 mm | 3273 mm | 3251 mm | 3280 mm | 3223 mm | 3222 mm |
| Width over Tires – Maximum (loaded)* | 3297 mm | 3292 mm | 3273 mm | 3292 mm | 3241 mm | 3242 mm |
| Change in Vertical Dimensions (average of front and rear) | -8 mm | -36 mm | 19 mm | -24 mm | 16 mm | -20 mm |
| Change in Horizontal Reach | 3 mm | 23 mm | -10 mm | 20 mm | -4 mm | 28 mm |
| Change in Clearance Circle to Outside of Tires | 32 mm | 27 mm | 9 mm | 27 mm | -24 mm | -22 mm |
| Change in Clearance Circle to Inside of Tires | -32 mm | -27 mm | -9 mm | -27 mm | 24 mm | 22 mm |
| Change in Operating Weight (without Ballast) | 208 kg | -700 kg | 708 kg | -608 kg | -320 kg | -844 kg |
| Change in Static Tipping Load – Straight | 157 kg | -528 kg | 535 kg | -459 kg | -242 kg | -637 kg |
| Change in Static Tipping Load – Articulated | 137 kg | -460 kg | 465 kg | -399 kg | -210 kg | -555 kg |

*Width over tire bulge and includes tire growth.

NOTE: Changes compared to 980M with Bridgestone 29.5R25 VSNT L4 tires.

982M Tire Option Chart

| Tire Brand | Michelin | Bridgestone | Bridgestone |
|---|------------------|------------------|----------------|
| Tire Size | 875/65R29 | 875/65R29 | 29.5R29 |
| Tread Type | L-3 | L-3 | L-5 |
| Tread Pattern | XHA2 | VTS | VSDL |
| Width over Tires – Maximum (unloaded)* | 3473 mm | 3447 mm | 3425 mm |
| Width over Tires – Maximum (loaded)* | 3504 mm | 3472 mm | 3448 mm |
| Change in Vertical Dimensions (average of front and rear) | -6 mm | -7 mm | 82 mm |
| Change in Horizontal Reach | -1 mm | 2 mm | -70 mm |
| Change in Clearance Circle to Outside of Tires | 28 mm | -4 mm | -28 mm |
| Change in Clearance Circle to Inside of Tires | -28 mm | 4 mm | 28 mm |
| Change in Operating Weight (without Ballast) | -356 kg | -76 kg | 1008 kg |
| Change in Static Tipping Load – Straight | -236 kg | -50 kg | 667 kg |
| Change in Static Tipping Load – Articulated | -206 kg | -44 kg | 583 kg |

*Width over tire bulge and includes tire growth.

NOTE: Changes compared to 982M with Bridgestone 875/65R29 VLTS L4 tires.

980M/982M Wheel Loaders Specifications

980M Bucket Fill Factors Chart


The bucket size must be chosen based on the density of the material and on the expected fill factor. The new Cat Performance Series Buckets with longer floor, larger bucket opening, increased repository angle, rounded side boards and integrated spill guard, demonstrate fill factors significantly higher than previous generation or non Cat buckets. The actual volume handled by the machine is thus often larger than the rated capacity.

| Loose Material | | Fill Factor (%)* | Material Density |
|-----------------|-------------------|------------------|------------------|
| Earth/Clay | | 115 | 1.5-1.7 |
| Sand and Gravel | | 115 | 1.5-1.7 |
| Aggregate: | 25-76 mm | 110 | 1.6-1.7 |
| | 19 mm and smaller | 105 | 1.8 |
| Rock: | 76 mm and larger | 100 | 1.6 |

*As a % of ISO rated capacity.

Note: Fill Factors achieved will also depend on whether the product is washed or not washed.


980M Bucket Selection Chart



Note: All buckets are showing GET.

980M/982M Wheel Loaders Specifications

980M Operating Specifications with Buckets

| Linkage | | Standard Linkage | | | | | | High Lift Linkage Change** |
|--|----------------|---|--------------------|-----------------------|--------------------|-----------------------|--------------------|----------------------------|
| Pin/Quick Coupler | |  | | | | | | |
| Bucket Type | | General Purpose | | | | | | |
| Edge Type | | Bolt-On Cutting Edges | Teeth and Segments | Bolt-On Cutting Edges | Teeth and Segments | Bolt-On Cutting Edges | Teeth and Segments | |
| Capacity – Rated | m ³ | 5.4 | 5.4 | 5.7 | 5.7 | 6.0 | 6.0 | — |
| Capacity – Rated at 110% Fill Factor | m ³ | 5.9 | 5.9 | 6.3 | 6.3 | 6.6 | 6.6 | — |
| Width | mm | 3447 | 3535 | 3447 | 3535 | 3447 | 3535 | — |
| 16 † Dump Clearance at Maximum Lift and 45° Discharge | mm | 3273 | 3107 | 3204 | 3037 | 3187 | 3019 | 221 |
| 17 † Reach at Maximum Lift and 45° Discharge | mm | 1481 | 1618 | 1529 | 1663 | 1550 | 1685 | 3 |
| Reach at Level Lift Arm and Bucket Level | mm | 2965 | 3177 | 3049 | 3261 | 3077 | 3289 | 160 |
| A † Digging Depth | mm | 103 | 103 | 103 | 103 | 103 | 103 | -2 |
| 12 † Overall Length | mm | 9493 | 9734 | 9577 | 9818 | 9605 | 9846 | 201 |
| B † Overall Height with Bucket at Maximum Lift | mm | 6421 | 6421 | 6243 | 6243 | 6269 | 6269 | 221 |
| Loader Clearance Circle Radius with Bucket at Carry Position | mm | 7612 | 7726 | 7635 | 7749 | 7643 | 7757 | 1009 |
| Static Tipping Load, Straight (ISO)* | kg | 22 639 | 22 453 | 22 391 | 22 204 | 22 249 | 22 062 | -1939 |
| Static Tipping Load, Straight (Rigid Tire)* | kg | 24 023 | 23 835 | 23 775 | 23 586 | 23 635 | 23 446 | -2145 |
| Static Tipping Load, Articulated (ISO)* | kg | 19 565 | 19 379 | 19 334 | 19 147 | 19 197 | 19 009 | -1321 |
| Static Tipping Load, Articulated (Rigid Tire)* | kg | 20 796 | 20 608 | 20 567 | 20 378 | 20 432 | 20 243 | -1500 |
| Breakout Force*** | kN | 226 | 224 | 213 | 211 | 209 | 207 | 17 |
| Operating Weight* | kg | 30 090 | 30 228 | 30 173 | 30 311 | 30 269 | 30 407 | 115 |

*Static tipping loads and operating weights shown are based on a machine configuration with Bridgestone 29.5R25 VSNT L4 radial tires, full fluids, operator, standard counterweight, roading fenders, Product Link, open differential axles (front/rear), power train guard, secondary steering and sound suppression.

**Maximum values.

***Measured 102 mm behind tip of cutting edge with bucket hinge pin as pivot in accordance with SAE J732C.

Specifications and ratings conform to all applicable standards recommended by the Society of Automotive Engineers, including SAE Standard J732C governing loader ratings.

(With Tire Deflection) Full compliance to ISO 14397-1 (2007) Sections 1 thru 6, which requires 2% verification between calculations and testing.


(No Tire Deflection) Compliance to ISO 14397-1 (2007) Sections 1 thru 5.

†Illustration shown with Dimension charts.

Other buckets are available and offerings vary by region. Consult your local Cat dealer for further details.

980M/982M Wheel Loaders Specifications

980M Operating Specifications with Buckets

| Linkage | Standard Linkage | | | | | High Lift Linkage Change** |
|--|--|--------------------|--------------------|--------|--------|----------------------------|
| Pin/Quick Coupler |  | | | | | |
| | Pin On | | | | | |
| Bucket Type | Material Handling | | Rock | | | |
| Edge Type | Bolt-On Cutting Edges | Teeth and Segments | Teeth and Segments | Teeth | | |
| Capacity – Rated | m ³ | 5.7 | 5.7 | 4.5 | 5.4 | — |
| Capacity – Rated at 110% Fill Factor | m ³ | 6.3 | 6.3 | 5.0 | 5.9 | — |
| Width | mm | 3447 | 3535 | 3504 | 3504 | — |
| 16 † Dump Clearance at Maximum Lift and 45° Discharge | mm | 3105 | 2928 | 3051 | 2890 | 221 |
| 17 † Reach at Maximum Lift and 45° Discharge | mm | 1444 | 1566 | 1713 | 1904 | 3 |
| Reach at Level Lift Arm and Bucket Level | mm | 3074 | 3286 | 3284 | 3533 | 160 |
| A † Digging Depth | mm | 103 | 103 | 106 | 71 | -2 |
| 12 † Overall Length | mm | 9602 | 9843 | 9827 | 10 076 | 201 |
| B † Overall Height with Bucket at Maximum Lift | mm | 6242 | 6242 | 6204 | 6378 | 221 |
| Loader Clearance Circle Radius with Bucket at Carry Position | mm | 7642 | 7756 | 7734 | 7807 | 1009 |
| Static Tipping Load, Straight (ISO)* | kg | 21 892 | 21 708 | 22 740 | 22 412 | -1939 |
| Static Tipping Load, Straight (Rigid Tire)* | kg | 23 234 | 23 048 | 24 137 | 23 824 | -2145 |
| Static Tipping Load, Articulated (ISO)* | kg | 18 888 | 18 704 | 19 589 | 19 299 | -1321 |
| Static Tipping Load, Articulated (Rigid Tire)* | kg | 20 084 | 19 897 | 20 830 | 20 557 | -1500 |
| Breakout Force*** | kN | 210 | 207 | 210 | 193 | 17 |
| Operating Weight* | kg | 30 298 | 30 436 | 30 978 | 31 024 | 115 |

*Static tipping loads and operating weights shown are based on a machine configuration with Bridgestone 29.5R25 VSNT L4 radial tires, full fluids, operator, standard counterweight, roading fenders, Product Link, open differential axles (front/rear), power train guard, secondary steering and sound suppression.

**Maximum values.

***Measured 102 mm behind tip of cutting edge with bucket hinge pin as pivot in accordance with SAE J732C.

Specifications and ratings conform to all applicable standards recommended by the Society of Automotive Engineers, including SAE Standard J732C governing loader ratings.

(With Tire Deflection) Full compliance to ISO 14397-1 (2007) Sections 1 thru 6, which requires 2% verification between calculations and testing.


(No Tire Deflection) Compliance to ISO 14397-1 (2007) Sections 1 thru 5.

†Illustration shown with Dimension charts.

Other buckets are available and offerings vary by region. Consult your local Cat dealer for further details.

980M/982M Wheel Loaders Specifications

980M Operating Specifications with Buckets – Aggregate Handler

| Linkage | Aggregate Handler | | | |
|--|---|--------|-----------------------|-------------------|
| Pin/Quick Coupler |  | | | |
| | General Purpose | | | Material Handling |
| Bucket Type | Bolt-On Cutting Edges | | Bolt-On Cutting Edges | |
| Edge Type | Bolt-On Cutting Edges | | Bolt-On Cutting Edges | |
| Capacity – Rated | m ³ | 5.7 | 6.0 | 5.7 |
| Capacity – Rated at 110% Fill Factor | m ³ | 6.3 | 6.6 | 6.3 |
| Width | mm | 3447 | 3447 | 3447 |
| 16 † Dump Clearance at Maximum Lift and 45° Discharge | mm | 3204 | 3187 | 3105 |
| 17 † Reach at Maximum Lift and 45° Discharge | mm | 1529 | 1550 | 1444 |
| Reach at Level Lift Arm and Bucket Level | mm | 3049 | 3077 | 3074 |
| A † Digging Depth | mm | 103 | 103 | 103 |
| 12 † Overall Length | mm | 9638 | 9666 | 9663 |
| B † Overall Height with Bucket at Maximum Lift | mm | 6243 | 6269 | 6242 |
| Loader Clearance Circle Radius with Bucket at Carry Position | mm | 7635 | 7643 | 7642 |
| Static Tipping Load, Straight (ISO)* | kg | 23 972 | 23 827 | 23 447 |
| Static Tipping Load, Straight (Rigid Tire)* | kg | 25 481 | 25 339 | 24 909 |
| Static Tipping Load, Articulated (ISO)* | kg | 20 630 | 20 491 | 20 163 |
| Static Tipping Load, Articulated (Rigid Tire)* | kg | 21 997 | 21 860 | 21 488 |
| Breakout Force** | kN | 213 | 209 | 210 |
| Operating Weight* | kg | 30 822 | 30 918 | 30 947 |

*Static tipping loads and operating weights shown are based on a machine configuration with Bridgestone 29.5R25 VSNT L4 radial tires, full fluids, operator, aggregate counterweight, roading fenders, Product Link, open differential axles (front/rear), power train guard, secondary steering and sound suppression.

**Measured 102 mm behind tip of cutting edge with bucket hinge pin as pivot in accordance with SAE J732C.

Specifications and ratings conform to all applicable standards recommended by the Society of Automotive Engineers, including SAE Standard J732C governing loader ratings.

(With Tire Deflection) Full compliance to ISO 14397-1 (2007) Sections 1 thru 6, which requires 2% verification between calculations and testing.

(No Tire Deflection) Compliance to ISO 14397-1 (2007) Sections 1 thru 5.

†Illustration shown with Dimension charts.

Aggregate Handler configuration is not compatible with teeth and segments, tips, rock buckets, high lift, and L5 tires.

Other buckets are available and offerings vary by region. Consult your local Cat dealer for further details.

980M/982M Wheel Loaders Specifications

982M Bucket Fill Factors Chart


The bucket size must be chosen based on the density of the material and on the expected fill factor. The new Cat Performance Series Buckets with longer floor, larger bucket opening, increased repository angle, rounded side boards and integrated spill guard, demonstrate fill factors significantly higher than previous generation or non Cat buckets. The actual volume handled by the machine is thus often larger than the rated capacity.

| Loose Material | | Fill Factor (%)* | Material Density |
|-----------------|-------------------|------------------|------------------|
| Earth/Clay | | 115 | 1.5-1.7 |
| Sand and Gravel | | 115 | 1.5-1.7 |
| Aggregate: | 25-76 mm | 110 | 1.6-1.7 |
| | 19 mm and smaller | 105 | 1.8 |
| Rock: | 76 mm and larger | 100 | 1.6 |

*As a % of ISO rated capacity.

Note: Fill Factors achieved will also depend on whether the product is washed or not washed.

982M Bucket Selection Chart




Note: All buckets are showing GET.

Note: Aggregate Handler configuration is not compatible with teeth and segments, tips, rock buckets, high lift, and L5 tires.

980M/982M Wheel Loaders Specifications

982M Operating Specifications with Buckets

| Linkage | | Standard Linkage | | | | |
|--|----------------|---|--------------------|-----------------------|--------------------|-----------------------|
| Pin/Quick Coupler | |  | | | | |
| Bucket Type | | General Purpose | | | | |
| Edge Type | | Bolt-On Cutting Edges | Teeth and Segments | Bolt-On Cutting Edges | Teeth and Segments | Bolt-On Cutting Edges |
| Capacity – Rated | m ³ | 6.1 | 6.1 | 6.4 | 6.4 | 7.0 |
| Capacity – Rated at 110% Fill Factor | m ³ | 6.7 | 6.7 | 7.0 | 7.0 | 7.7 |
| Width | mm | 3602 | 3665 | 3602 | 3665 | 3588 |
| 16 † Dump Clearance at Maximum Lift and 45° Discharge | mm | 3365 | 3197 | 3327 | 3159 | 3297 |
| 17 † Reach at Maximum Lift and 45° Discharge | mm | 1569 | 1703 | 1602 | 1735 | 1623 |
| Reach at Level Lift Arm and Bucket Level | mm | 3257 | 3468 | 3307 | 3518 | 3345 |
| A † Digging Depth | mm | 116 | 116 | 116 | 116 | 116 |
| 12 † Overall Length | mm | 10 168 | 10 403 | 10 218 | 10 453 | 10 256 |
| B † Overall Height with Bucket at Maximum Lift | mm | 6592 | 6592 | 6642 | 6642 | 6709 |
| Loader Clearance Circle Radius with Bucket at Carry Position | mm | 7885 | 7993 | 7900 | 8009 | 7906 |
| Static Tipping Load, Straight (ISO)* | kg | 24 791 | 24 692 | 24 583 | 24 483 | 24 420 |
| Static Tipping Load, Straight (Rigid Tire)* | kg | 26 101 | 26 001 | 25 901 | 25 800 | 25 747 |
| Static Tipping Load, Articulated (ISO)* | kg | 21 080 | 20 981 | 20 881 | 20 781 | 20 728 |
| Static Tipping Load, Articulated (Rigid Tire)* | kg | 22 393 | 22 293 | 22 201 | 22 101 | 22 056 |
| Breakout Force** | kN | 262 | 262 | 253 | 253 | 247 |
| Operating Weight* | kg | 35 564 | 35 636 | 35 695 | 35 767 | 35 768 |

*Static tipping loads and operating weights shown are based on a machine configuration with Bridgestone 875/65R29 VLTS L4 radial tires, full fluids, operator, standard counterweight, cold start, roading fenders, Product Link, open differential axles (front/rear), power train guard, secondary steering and sound suppression.

**Measured 102 mm behind tip of cutting edge with bucket hinge pin as pivot in accordance with SAE J732C.

Specifications and ratings conform to all applicable standards recommended by the Society of Automotive Engineers, including SAE Standard J732C governing loader ratings.

(With Tire Deflection) Full compliance to ISO 14397-1 (2007) Sections 1 thru 6, which requires 2% verification between calculations and testing.


(No Tire Deflection) Compliance to ISO 14397-1 (2007) Sections 1 thru 5.

†Illustration shown with Dimension charts.

Other buckets are available and offerings vary by region. Consult your local Cat dealer for further details.

980M/982M Wheel Loaders Specifications

982M Operating Specifications with Buckets

| Linkage | | Standard Linkage | | | |
|--|----------------|---|--------------------|-----------------------|--------------------|
| Pin/Quick Coupler | |  | | | |
| Bucket Type | | Heavy Duty Rock | | | |
| Edge Type | | Bolt-On Cutting Edges | Teeth and Segments | Bolt-On Cutting Edges | Teeth and Segments |
| Capacity – Rated | m ³ | 5.4 | 5.4 | 5.8 | 5.8 |
| Capacity – Rated at 110% Fill Factor | m ³ | 5.9 | 5.9 | 6.4 | 6.4 |
| Width | mm | 3648 | 3648 | 3648 | 3648 |
| 16 † Dump Clearance at Maximum Lift and 45° Discharge | mm | 3336 | 3219 | 3293 | 3175 |
| 17 † Reach at Maximum Lift and 45° Discharge | mm | 1724 | 1845 | 1749 | 1869 |
| Reach at Level Lift Arm and Bucket Level | mm | 3419 | 3587 | 3469 | 3637 |
| A † Digging Depth | mm | 25 | 25 | 25 | 25 |
| 12 † Overall Length | mm | 10 347 | 10 524 | 10 397 | 10 574 |
| B † Overall Height with Bucket at Maximum Lift | mm | 6622 | 6622 | 6667 | 6667 |
| Loader Clearance Circle Radius with Bucket at Carry Position | mm | 7974 | 8035 | 7991 | 8052 |
| Static Tipping Load, Straight (ISO)* | kg | 24 599 | 24 468 | 24 554 | 24 284 |
| Static Tipping Load, Straight (Rigid Tire)* | kg | 25 954 | 25 822 | 25 927 | 25 643 |
| Static Tipping Load, Articulated (ISO)* | kg | 20 768 | 20 637 | 20 709 | 20 460 |
| Static Tipping Load, Articulated (Rigid Tire)* | kg | 22 127 | 21 994 | 22 084 | 21 823 |
| Breakout Force** | kN | 234 | 234 | 227 | 226 |
| Operating Weight* | kg | 37 617 | 37 710 | 37 726 | 37 818 |

*Static tipping loads and operating weights shown are based on a machine configuration with Bridgestone 875/65R29 VLTS L4 radial tires, full fluids, operator, standard counterweight, cold start, roading fenders, Product Link, open differential axles (front/rear), power train guard, secondary steering and sound suppression.

**Measured 102 mm behind tip of cutting edge with bucket hinge pin as pivot in accordance with SAE J732C.

Specifications and ratings conform to all applicable standards recommended by the Society of Automotive Engineers, including SAE Standard J732C governing loader ratings.

(With Tire Deflection) Full compliance to ISO 14397-1 (2007) Sections 1 thru 6, which requires 2% verification between calculations and testing.


(No Tire Deflection) Compliance to ISO 14397-1 (2007) Sections 1 thru 5.

†Illustration shown with Dimension charts.

Other buckets are available and offerings vary by region. Consult your local Cat dealer for further details.

980M/982M Wheel Loaders Specifications

982M Operating Specifications with Buckets – Aggregate Handler

| Linkage | Aggregate Handler | | | |
|--|---|--------------------|-----------------------|--------|
| Pin/Quick Coupler |  | | | |
| | Pin On | | | |
| Bucket Type | General Purpose | | | |
| Edge Type | Bolt-On Cutting Edges | Teeth and Segments | Bolt-On Cutting Edges | |
| Capacity – Rated | m ³ | 6.4 | 6.4 | 7.0 |
| Capacity – Rated at 110% Fill Factor | m ³ | 7.0 | 7.0 | 7.7 |
| Width | mm | 3602 | 3665 | 3588 |
| 16 † Dump Clearance at Maximum Lift and 45° Discharge | mm | 3327 | 3159 | 3297 |
| 17 † Reach at Maximum Lift and 45° Discharge | mm | 1602 | 1735 | 1623 |
| Reach at Level Lift Arm and Bucket Level | mm | 3307 | 3518 | 3345 |
| A † Digging Depth | mm | 116 | 116 | 116 |
| 12 † Overall Length | mm | 10 325 | 10 560 | 10 363 |
| B † Overall Height with Bucket at Maximum Lift | mm | 6642 | 6642 | 6709 |
| Loader Clearance Circle Radius with Bucket at Carry Position | mm | 7900 | 8009 | 7906 |
| Static Tipping Load, Straight (ISO)* | kg | 26 001 | 25 901 | 25 833 |
| Static Tipping Load, Straight (Rigid Tire)* | kg | 27 416 | 27 316 | 27 258 |
| Static Tipping Load, Articulated (ISO)* | kg | 22 045 | 21 946 | 21 888 |
| Static Tipping Load, Articulated (Rigid Tire)* | kg | 23 469 | 23 369 | 23 321 |
| Breakout Force** | kN | 253 | 253 | 247 |
| Operating Weight* | kg | 36 342 | 36 414 | 36 415 |

*Static tipping loads and operating weights shown are based on a machine configuration with Bridgestone 875/65R29 VLTS L4 radial tires, full fluids, operator, aggregate counterweight, cold start, roading fenders, Product Link, open differential axles (front/rear), power train guard, secondary steering and sound suppression.

**Measured 102 mm behind tip of cutting edge with bucket hinge pin as pivot in accordance with SAE J732C.

Specifications and ratings conform to all applicable standards recommended by the Society of Automotive Engineers, including SAE Standard J732C governing loader ratings.

(With Tire Deflection) Full compliance to ISO 14397-1 (2007) Sections 1 thru 6, which requires 2% verification between calculations and testing.

(No Tire Deflection) Compliance to ISO 14397-1 (2007) Sections 1 thru 5.

†Illustration shown with Dimension charts.

Aggregate Handler configuration is not compatible with teeth and segments, tips, rock buckets, high lift, and L5 tires.

Other buckets are available and offerings vary by region. Consult your local Cat dealer for further details.

980M/982M Standard Equipment

Standard Equipment

Standard equipment may vary. Consult your Cat dealer for details.

OPERATOR ENVIRONMENT

- Cab, pressurized and sound suppressed (ROPS/FOPS)
- Viscous mounts
- Multi-function 18 cm color LCD touch-screen display for rear vision camera image display (reverse travel activated) and machine status, setting and health parameters
- EH controls, SAL (single axis levers) lift and tilt function
- Steering, EH joystick, speed sensing with force feedback
- Radio ready (entertainment) includes antenna, speakers and converter (12V, 10-amp)
- Air conditioner, heater, and defroster (auto temp and fan)
- EH parking brake
- Beverage holders (2) with storage compartment for cell phone/MP3 player
- Bucket/work tool function lockout
- Coat hook (2)
- Cab air filter
- Ergonomic cab access ladders and handrails
- Horn, electric
- Light, two dome (cab)
- Mirrors, rearview external with integrated spot mirrors
- Post mounted membrane 16 switch keypad
- 3 receptacles, 12V
- Seat, Cat Comfort (cloth) air suspension
- Seat belt, 51 mm retractable, with indicator
- Steering, secondary
- Sun visor, front
- Wet-arm wipers/washers front and rear, intermittent front wiper
- Window, sliding (left and right sides)
- Cab tie-off

COMPUTERIZED MONITORING SYSTEM

- With following gauges:
 - Speedometer/tachometer
 - Digital gear range indicator
 - Diesel Exhaust Fluid (DEF) level
 - Temperature: engine coolant, hydraulic oil, transmission oil
 - Fuel level

- With following warning indicators:
 - Regeneration
 - Temperature: axle oil, engine intake manifold
 - Pressure: engine oil, fuel pressure hi/low, primary steering oil, service brake oil
 - Battery voltage hi/low
 - Engine air filter restriction
 - Hydraulic oil filter restriction
 - Hydraulic oil low
 - Parking brake
 - DEF low level
 - Transmission filter bypass

ELECTRICAL AND LIGHTING

- Batteries (2), maintenance free 1,400 CCA
- Ignition key; start/stop switch
- Starter, electric, heavy duty
- Starting and charging system (24V)
- Lighting system:
 - Four halogen work lights (cab mounted)
 - Two halogen roading lights (with signals)
 - Two halogen rear vision lights (hood mounted)
- Alarm, back-up
- Alternator, 145-amp brushed
- Main disconnect switch
- Receptacle start (cables not included)

CAT CONNECT TECHNOLOGIES

- Link technologies: Product Link
- Detect technologies: rear vision camera

POWER TRAIN

- Engine, Cat C13 ACERT meets Japan 2014 (Tier 4 Final) emission standards
- Cat Clean Emissions Module (CEM) with Diesel Particulate Filter (DPF) and remote Diesel Exhaust Fluid (DEF) tank and pump
- Fuel priming pump (electric)
- Fuel/water separator
- Precleaner, engine air intake
- Economy Mode (selectable)
- Transmission, automatic planetary power shift (4F/4R)
- Torque converter, locking clutch with free wheel stator
- Switch, transmission neutralizer lockout
- Axles, open differential, front and rear
- Heavy duty transmission (982M)
- Axles, ecology drains

- Brakes, full hydraulic enclosed wet-disc with Integrated Braking System (IBS)
- Brake wear indicators
- Parking brake, disc and caliper
- Fan, radiator, electronically controlled, hydraulically driven, temperature sensing, on demand
- Radiator, high debris, 6 fins per inch, 43° cooling capacity

LINKAGE

- Linkage, Z-bar, cast crosstube/tilt levers
- Kickout, lift and tilt, automatic (adjustable in cab)

HYDRAULICS

- Hydraulic system, load sensing
- Steering, load sensing
- Ride control, 2V
- Remote diagnostic pressure taps
- Hoses, Cat XT™
- Couplings, Cat O-ring face seal
- Hydraulic oil cooler (swing out)
- Oil sampling valves

FLUIDS

- Premixed extended life coolant with freeze protection to -34° C

OTHER STANDARD EQUIPMENT

- One-piece tilting hood with side and rear doors
- Service centers (electrical and hydraulic)
- Platform, window washing
- Auto idle shutdown
- Fenders, steel front with mud-flap/rear with extension
- Guard, power train
- Ecology drains for engine, transmission, and hydraulics
- Ether aid ready
- Grill, airborne debris
- Filters: fuel, engine air, engine oil, hydraulic oil, transmission
- Fuel cooler
- Grease zerks
- Hitch, drawbar with pin
- Precleaner rain cap
- Sight gauges: engine coolant, hydraulic oil, and transmission oil level
- Toolbox
- Vandalism protection caplocks

Optional Equipment

Optional equipment may vary. Consult your Cat dealer for details.

OPERATOR ENVIRONMENT

- Door, remote opening system
- Cover, HVAC metallic
- EH controls, SAL 3rd function
- EH controls, joystick lift and tilt
 - Additional integrated roller switches for 3rd function
- Filter, carbon fresh air
- Mirrors, heated rearview external with integrated spot mirrors
- Precleaner, HVAC
- Precleaner, HVAC (RESPA)
- Radio, AM/FM/CD/USB/MP3 Bluetooth
- Seat, heated air suspension
- Steering, EH wheel with directional FNR shifter and gear selector
 - Additional FNR with implement controls
- Roof, metallic
- Sun visor, rear
- Windows, rubber mounted
- Windows, with front guard
- Windows, with heavy duty front guard
- Windows, with full guards front, rear and sides

ELECTRICAL AND LIGHTING

- Four additional auxiliary halogen cab mounted work lights or
- Two additional auxiliary front HI LED and two additional auxiliary rear LED cab mounted work lights with two LED work lights in the radiator grill and LED front turn signals also includes replacement of the standard four halogen cab mounted work lights with four LED work lights (the standard offering and only roading light available is the halogen roading light)
- Warning amber strobe beacon
- Reversing strobes
- External seat belt indicator light

STARTERS, BATTERIES, AND ALTERNATORS

- Batteries (4), maintenance free 1,400 CCA With 240V Engine Coolant Heater

CAT CONNECT TECHNOLOGIES

- Cat Object Detection
- Link technologies: VIMS™
- Payload technologies:
 - Aggregate Autodig
 - Cat Production Measurement
 - Printer, Cat Production Measurement
- Detect technologies: dedicated display for rear vision camera, full-time activation
- Machine Security System

POWER TRAIN

- Axles
 - Differentials: limited slip, front or rear
 - Axle oil cooler
- Heavy duty transmission (980M)
- Fan, VPF (variable pitch fan), automatic and manual control
- Radiator, low debris, 9 fins per inch, high ambient 47° cooling capacity

LINKAGE

- High lift (980M)
- Logger (980M)
- Steel Mill (980M)
- Quick coupler ready

WORK TOOLS

- Performance Series buckets
- Forks, pallet
- Forks, logging

HYDRAULICS

- 3rd function with Ride Control
 - Standard linkage
 - High lift linkage (980M)
 - Logger linkage (980M)
 - Steel Mill (980M)

OTHER OPTIONAL EQUIPMENT

- Fenders, roading
- Fuel tank, fast fill
- Precleaner, turbine
- Precleaner, trash

OTHER OPTIONAL CONFIGURATIONS

- High Lift (980M)
- Steel Mill (980M)
- Logger (980M)
- Industrial (980M)
- Aggregate Handler (980M, 982M)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

AEHQ8005 (02-2017)
(Japan)

© 2017 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

Based on the Labor, Safety and Health Laws in Japan, employer of small construction equipment are required to provide specific training for all operators on machines with ship weight less than 3 metric ton. For machines greater than 3 metric ton, operator needs to obtain operator license certification from a Government approved registered training school.

