



Husqvarna K 4000

This electric all-round cutter minimises the amount of water and slurry. Unlike other electric cutters, the blade rotates forward, cutting into the material efficiently with minimum effort on the operator. K 4000 is easily adaptable for dry cutting with the Vac attachment accessory for minimal dust generation.



Increased productivity

The new pop-up carbon brushes protect the collector from unforeseen rotor changes which increases reliability and enables longer service intervals.



Ergonomically designed rear handle

Power cord inlet located underneath the handle enables ease of use and comfortable handling with hassle free operation.

Constant-flow water valve

The integrated regulator controls the water volume, ensuring a constant flow to the blade. It also ensures the amount of water is sufficient to bind the dust without creating an excess of water.



Easy serviceability

The one-piece inspection lid and Torx screws make it easy to assemble and service.



FEATURES

- The integrated regulator controls the water volume, ensuring a constant flow to the blade. It also ensures the amount of water is sufficient to bind the dust without creating an excess of water.
- Ergonomically designed rear handle
- Increased productivity
- Easy serviceability
- Quick acting locks for the spindle and a large outlet in the blade guard simplifies blade replacement.
- The blade on all of our electric cutters rotates forward, cutting into the material efficiently, minimizing the risk of sticking and kickbacks.
- Generously dimensioned miter gear provides high durability, minimal power loss and low noise levels.
- Our Elgard™ system protects against overload by varying the rotation speed.
- A powerful electric cutter for both indoor and outdoor use
- The advanced electronic overload protection varies the rotation speed to warn of approaching overload.
- Provides starting with normal, slow acting fuses.
- Cutting for minor adjustments to window and door openings.
- Cutting building blocks, curbstones and garden pavers.
- Cutting cast concrete.
- Irregular deep cutting.
- Regular cutting in floors and walls.
- Cutting grooves for expansion joints and crack repair.
- Deep cutting in pipe trenches.
- Pipe cutting.

Technical Specifications	
CAPACITY	
Output shaft RPM, max	3400 rpm
Peripheral speed, max	19690 fpm
Rated input power	2.4 hp
Water pressure, max	116 psi
DIMENSIONS	
Article gross weight	10400 g
Article net weight	10000 g
Arbor diameter	1 in
Blade diameter, max	14 in
Blade flange diameter	4.1 in
Blade thickness, max	0.22 in
Cutting depth, max	5 in
Product size height	12.3 in
Product size length	24.8 in
Product size width	8.7 in
Weight	16.8 lbs
ENGINE	
Electronic product	Yes
Engine cooling	Fan/Air
Max engine/motor RPM	19350 rpm
EQUIPMENT	
Phases	1 ph
Plug	IEC type B
Rated current	15 A
Water connector	Garderna Male
LUBRICANTS	
Engine cooling	Fan/Air
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	105 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	95 dB(A)
VIBRATIONS	
Daily Vibration (Aeqv)	3.5 m/s ²
Daily Vibration Exposure (A8)	1.24 m/s ²
Daily Vibration Time (Time factor)	1 h
Vibrations left/front handle	3.5 m/s ²
Vibrations right/rear handle	3.5 m/s ²
PACKAGING	
Packaging length	775 mm
Packaging width	280 mm
Packaging height	255 mm

ACCESSORIES



PRESSURIZED WATER TANK
506 32 63-02



WT 15
966 70 83-02



HUSQVARNA WT2GO
598 74 24-01