



Husqvarna TS 60

A robust tile saw with a refined cart and rail system for perfectly straight cuts. The TS 60 is equipped with a patented water and slurry system for little to no mess. This includes an efficient recycling system that cleans water for reuse. Also, Elgard™ warns you of an approaching overload, and Electronic SoftStart™ allows starting with normal, slow acting fuses.



Flexible cutting method

Switches between plunge cuts and mitre cuts with ease.



Easy transport

The low weight, foldable legs and stable wheels facilitate transportation.

Clean work area

The Jet Stream Water Containment System keeps water and slurry in the cart trench, making it ideal for cutting indoors.



Ideal for long cutting

The maximum cutting length of 700 mm and the large cutting table allows you to cut 50x50 cm tiles diagonally.



FEATURES

- The Jet Stream Water Containment System keeps water and slurry in the cart trench, making it ideal for cutting indoors.
- The low weight, foldable legs and stable wheels facilitate transportation.
- Switches between plunge cuts and mitre cuts with ease.
- The maximum cutting length of 700 mm and the large cutting table allows you to cut 50x50 cm tiles diagonally.
- The large removable cutting table is easy to clean.
- Thanks to the refined recycling system which cleans water for reuse.
- Keeps water and slurry in the cart trench, making it ideal for cutting indoors.
- Enables bevel cuts between 22.5 and 45 degrees.
- The Elgard™ overload protection system allows you to always cut at maximum speed, for best performance.
- LED indication for machine overload provides increased productivity and motor life.
- Angle guide and adjustable stand are included to facilitate cutting.
- Provides starting with normal, slow acting fuses.
- Softstart™ lowers incoming current to reduce amperage when starting the motor.

Technical Specifications

MOTOR	
Frequency	60 Hz
Voltage	120 V
Rated input power	1.7 kW
CUTTING EQUIPMENT	
Blade diameter, max	250 mm
Cutting depth, max	65 mm
Max cutting length	700 mm
Diagonal cut, max	0 mm
PACKAGING	
Packaging length	1000 mm
Packaging width	750 mm
Packaging height	700 mm
Packaging volume	411.3 dm ³